


Applied Polymer Systems, Inc.

Material Safety Data Sheet



1. IDENTIFICATION OF THE PRODUCT AND THE COMPANY

Product Name: APS 703d Flocc Log[®]

Supplied: Applied Polymer Systems, Inc.
519 Industrial Drive
Woodstock, GA 30189
Tel. 678-494-5998
Fax. 678-494-5298
www.siltstop.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Identification of the preparation: Anionic water-soluble Co-polymer gel

3. HAZARD IDENTIFICATION

Placement of these materials on wet walking surface will create extreme slipping hazard.

4. FIRST AID MEASURES

Inhalation: None

Skin contact: Contact with wet skin could cause dryness and chapping. Wash with water and soap.

Eye contact: Rinse thoroughly with plenty of water, also under the eyelids, seek medical attention in case of persistent irritation.

Ingestion: Consult a physician

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water, water spray, foam, carbon dioxide, dry powder.

Special fire-fighting precautions: Flocc Logs that become wet render surfaces extremely slippery.

Protective equipment for firefighters: No special equipment required.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: No special precautions required.

Methods for cleaning up: Dry wipe as well as possible. Keep in suitable and closed containers for disposal.
After cleaning, flush away traces with water.

7. HANDLING AND STORAGE

Handling: Avoid contact with skin and eyes. Wash hands after handling.

Storage: Keep in a cool, dry place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use dry handling areas only.

Personal protection equipment

Respiratory Protection: None
 Hand protection: Dry cloth, leather or rubber gloves.
 Eye Protection: Safety glasses with side shields. Do not wear contact lenses.
 Skin protection: No special protective clothing required.
 Hygiene measures: Wash hands before breaks and at end of work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Granular semi-solid gel
 Color: Blue
 Odor: None
 pH: 7.37
 Melting point: N/A
 Flash point: N/A
 Vapor density: N/A

10. STABILITY AND REACTIVITY

Stability: Product is stable, no hazardous polymerization will occur.
 Materials to avoid: Oxidizing agents may cause exothermic reactions.
 Hazardous decomposition products: Thermal decomposition may produce nitrogen oxides (NOx), carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute toxicity (EPA/600/4-90/027F)

LD 50 / *Rattus norvegicus* / oral / > 5000 mg/kg
 LC 50 / *Daphnia magna* / 48h / >383mg/L
 LC 50 / *Oncorhynchus mykiss* / 96h / 1900 mg/L

Chronic toxicity (EPA/600/4-91/002)

IC 25 (Survival) / <i>P. promelas</i> / 7 day / 110 ppm	IC 25 (Survival) / <i>C. dubia</i> / 7 day / 99.8 ppm
NOEC (Survival) / <i>P. promelas</i> / 7 day/ 105 ppm	NOEC (Survival) / <i>C. dubia</i> / 7 day/ 52.5 ppm
IC 25 (Growth) / <i>P. promelas</i> / 7 day / 130 ppm	IC 25 (Reproduction) / <i>C. dubia</i> / 7 day / 58.2 ppm
NOEC (Growth) / <i>P. promelas</i> / 7 day / 105 ppm	NOEC (Reproduction) / <i>C. dubia</i> / 7 day / 105 ppm

12. ECOLOGICAL INFORMATION

Fish: LC 50 / *Pimephales promelas* / 96h / >1000 mg/l
 Water Flea: LC 50 / *Daphnia magna* / 48h / 383mg/l
 Algae: EC 50 / *Selenastrum capricornutum* / 96h / >500mg/l

Bioaccumulation: The product is not expected to bioaccumulate.
 Persistence / degradability: Not readily biodegradable: (~85% after 180 days).

13. TRANSPORT AND REGULATORY INFORMATION

Not regulated by DOT, RCRA status-Not a hazardous waste

NFPA and HMIS ratings:

NFPA Health: 1	Flammability: 0	Reactivity: 0
HMIS Health 1	Flammability 0	Reactivity 0